



## Husqvarna FS 400 LV

*Robust, convenient all-round floor saw. The adjustable handle ensures low vibrations and an ergonomic working position. Also, perfect weight distribution means excellent stability while sawing.*



### RETRACTABLE HANDWHEEL

The handwheel can be folded when moving the saw to avoid breakage.



### LOW VIBRATION HANDLE

The adjustable handle ensures low vibrations and an ergonomic working position.



### DEPTH INDICATOR

Depth indicator displaying both millimeter and inches.



### LARGE WATERTANK

Large water tank made of impact-resistant plastic with quick connection for water hose to the upper part of the blade guard. No tools required for disassembly.

## Features Husqvarna FS 400 LV

- Husqvarna's floor saws are robust, well designed and easy to use thanks to features as protective cage, lift bail and cutting depth indicator.
- Patent-pending raise/lower assist system, using gas spring.
- Patent-pending engine and blade shaft mounting system give better cutting performance and also reduce vibrations, which makes work less tiring for the operator during long shifts.
- Very robust, productive saw with excellent weight distribution and stability.
- Adjustable, and low-vibration handlebar for operator comfort.
- Patent-pending assisted raise / lower system.
- Easy to transport and lift.
- Optimum power transmission to the blade thanks to the Poly-V belt.
- Large integrated water tank.

TECHNICAL SPECIFICATION	
Motor manufacturer	Honda
Motor spec	GX390
Max output (As rated by the engine manufacturer)	8.2 kW / 11 hp
Engine/motor RPM	pos1:3000 rpm
Cylinders	1
Number of strokes	4-stroke engine
Cylinder displacement	389 cm <sup>3</sup> / 23 cu.inch
Cylinder bore	88 mm / 3 inch
Cylinder stroke	64 mm / 2 inch
Fuel tank volume	6.1 lit / 1.61 gal.
Air filter type	Cyclone dry dual
Starter	Recoil
Engine cooling	Air
Belt	Poly V
Oil capacity, l	1.1 lit
Output RPM	3000 rpm
Diamond blade, max	450 mm / 18"
Max cutting depth	165 mm / 6.5 inch
Spindle diameter	25.4 mm / 1"
Blade depth control	Handwheel
Blade rotation	Downcut
Blade shaft drive	Poly-V belt
Blade flange	114.3 mm / 4.5"
Arbor size	25.4 mm / 1"
Axle front	20 mm / 0.79 inch
Handle bars	Fixed, low vibration
Primary wheel size	Outside diameter: 125 Wheel width: 35 Inner bore: 20 mm / Outside diameter: 4.92 Wheel width: 1.38 Inner bore: 0.79"
Secondary wheel size	Outside diameter: 200 Wheel width: 35 Inner bore: 20 mm / Outside diameter: 7.87 Wheel width: 1.38 Inner bore: 0.79"
Wheel description primary	Aluminium with bearings & seals
Wheel description secondary	Aluminium with bearings & seals
Blade guard attachment	Bolted
Blade guard capacity	457.2 mm / 18 inch
Blade guard type	Fixed
Water tank volume	30 lit / 7.9 gal.
Water safety device	Integrated water tank
Weight	99 kg / 218.25 lbs
Weight incl. packaging	125 kg / 275.57 lbs
Product size, LxWxH	1150x590x940 mm / 45.28x23.23x37.01 inch
Sound power level, guaranteed (LWA)	106 dB(A)
Sound pressure	96 dB(A)
Hand arm vibration (Aeq)	3 m/s <sup>2</sup>