



### ROLAIR STANDARD FEATURES

**PUMP:** ROLAIR Quality, Heavy-Duty, Single Stage, Ball Bearings, Cast-Iron Twin Cylinders, Cast-Iron Valve Plates with Swedish Lamellar Reed Valves, Aluminum Alloy Connecting Rods with Automotive-Style Inserts, Multi-Finned 11" Flywheel, Oil Sight Gauge and Splash Lubrication.

**ENGINE:** 6.5 HP Honda 4 Cycle, Complete Die Cast Aluminum Alloy with Cast-Iron Sleeve, Overhead Valves, Retractable Starter, On/Off Switch, Splash Lubricated, Low Oil Shutdown

**TANK ASSEMBLY:** Non-Code, 9 Gallons (optional 20 Gallon Tank)

**WHEELS:** One 410/350 x 4  
2-Ply Fully-Pneumatic *with Sealant*

**PERFORMANCE @ 100 PSI:**  
Cu. Ft. Displaced - 17.9  
Cu. Ft. Free Air - 13.1

**DIMENSIONS:**  
L46" x W19" x H28"

**APPROXIMATE SHIPPING WEIGHT:**  
179 lbs.

### STANDARD EQUIPMENT

- Automatic Pilot Valve Operation
- Industrial Flexible Discharge Hose
- Automatic Idle Control for Economy and Long Service Life
- 110/135 PSI Operating Pressure
- Air-Cooled Aftercooler
- Pressure Gauge 0-200 in 5 lb. Graduations
- Intake Filter with Silencer and Replaceable Element
- Schmidt Belt Tightening Device
- Safety Relief Valve
- Totally Enclosed Steel Belt Guard
- Accessory Support Bracket

### OPTIONAL EQUIPMENT

Filter-Regulator-Lubricator Sets, Robin Engines

### ROLAIR SYSTEMS

606 S. LAKE ST, P O BOX 346, HUSTISFORD WI 53034-0346  
SALES FAX: 920.349.3691 - SERVICE FAX: 920.349.8861  
PHONE: 920-349-3281

[www.rolair.com](http://www.rolair.com)

