

1150 All Wheel Loader

Item Number: 0620744

1150

All wheel steer loader delivers excellent maneuverability

>> The 1150 wheel loader from Wacker Neuson features a 4-wheel steer system and rigid frame design. An exceptional power to weight ratio makes these units very fuel efficient and economical to run. Powered by a turbo-charged Deutz engine, the 1150 wheel loader provides unmatched maneuverability and stability. The largest in the Wacker Neuson line of all wheel steer loaders, the 1150 delivers reliable performance to the job site. <<



Additional Advantages

- All wheel steer and rigid frame provide excellent maneuverability and constant payload stability even when turning.
- Hydraulically operated quick-hitch allows for efficient changing from one attachment to another without leaving the operator's station.
- Spacious operator station allows for excellent 360-degree visibility and ergonomics.
- All components for daily operation, maintenance and service work are easily reached due to the excellent accessibility.
- Single joystick operation allows for precise work with minimum effort and reduced fatigue.

Description	Metric	Imperial
Engine Make	Deutz	
Model	Water cooled 4-cylinder diesel engine	
Engine Type	TD2011	
Operating power according to DIN-ISO 3046*	58 kW	77.8 hp
Speed	0 - 20 km/h	0 - 12.4 mph
Bucket capacity	1,15 - 1,8 m ³	1.5 - 2.35 yd ³
Drive	Continuously variable hydrostatic axial-piston gear box	
Axles	Planetary steering axles-oscillating	
Oscillation	22 Max °	22 Max °
Differential lock	100% on front axle	
Brake Type	Working Hydrostatic/Mechanical Parking - Mechanical	Working- Hydrostatic/Mechanical Parking - Mechanical
Standard tires	405/70R24 Radial	
Overall length	5,8 mm	19.0 in
Width	1,95 m	6.42 ft
Height of canopy / cab	2,65 m	8.67 ft
Wheelbase	2,15 m	7.08 ft
Turning radius, bucket	4,05 m	13.25 ft
Turning radius - inside	0,96 m	3.17 in
Operating weight	5900 kg	13,007 lb
Work pump	Gear pump	
Hydraulic pump flow	84 l/min	22.2 US gpm
System pressure	250 bar	3626 psi
Loader Design	Parallel	
Hydraulic lifting capacity	4893 kg	10,787 lb
Breake-out force	43 kg	9667 lb
Tipping load with bucket	4140 kg	9127 lb
Tipping loads with pallet fork (straight)	3625 kg	7992 lb
Max. height of bucket pivot point	3,5 mm	11.5 in
Max. dump height	2,72 mm	8.92 in
Steering	All Wheel	
Steering angle	2 x 40 °	2 x 40 °
Fuel tank capacity	60 l	15.9 US gal
Hydraulic tank capacity	50 l	13.2 US gal

Standard Package - 1150

Operator's Manual

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Wednesday, September 5, 2012

