

280 280-LOADER,ALL WHL,CAB,HF

Item Number: 0620599

280

Excellent maneuverability and smooth all wheel drive.

>> The 280 wheel loader is ideally suited for work in confined areas not accessible by larger machines. Weighing in at 7,275 pounds, this compact unit offers easy transport and maneuverability around the job site. A long wheelbase ensures smooth driving and easy handling, even on rugged terrain. Counterweights are located far behind the rear axle for higher payloads. A single joystick control provides for operator comfort and easy operation. The all wheel steer offers tight cornering and consistent operating capacities allowing for full turns even on steep grades. <<



Additional Advantages

- Operator station is easily accessible from both sides for added convenience.
- Single joystick operation with pilot control allows for precise work with minimum effort for all functions.
- Adjustable steering column provides optimal operator comfort.
- Hydraulically operated quick-hitch allows for efficient changing from one accessory to another without leaving the operator's station.
- All wheel steer and rigid frame provide excellent maneuverability and constant payload stability even when turning.

| Description | Metric | Imperial |
|--|---|--|
| Engine Make | Yanmar | |
| Model | 4TNV88 | |
| Engine Type | Water cooled 4-cylinder diesel engine | |
| Operating power according to DIN-ISO 3046* | 28,8 kW | 38.6 hp |
| Speed | 0 - 20 km/h | 0 - 12 mph |
| Bucket capacity | 0,65 - 1,1 m ³ | 0.85 - 1.4 yd ³ |
| Drive | Continuously variable hydrostatic axial-piston gear box | |
| Axles | Planetary steering axles-oscillating | |
| Oscillation | 14 ° | 14 ° |
| Brake Type | Hydrostatic drive with mechanical disc brake | Hydrostatic drive with mechanical disc brake |
| Standard tires | 12,5 - 18 | |
| Length | 4,61 m | 15.1 ft |
| Width | 1,5 m | 4.9 ft |
| Height of canopy / cab | 2,34 m | 7.7 ft |
| Wheelbase | 1,75 m | 5.75 ft |
| Turning radius, bucket | 3,40 m | 11.16 ft |
| Turning radius, tires | 2,43 m | 8 ft |
| Turning radius, track circle | 2,28 m | 7.5 ft |
| Operating weight | 3200 kg | 7055 lb |
| Work pump | Gear pump | |
| Hydraulic pump flow | 52 l/min | 14 US gpm |
| System pressure | 240 bar | 3481 psi |
| Loader Design | Z-style with optimized parallel lift | |
| Hydraulic lifting capacity | 2855 kg | 6295 lb |
| Breake-out force | 2784 kg | 6137 lb |
| Tipping load with bucket | 2340 kg | 4409 lb |
| Tipping loads with pallet fork (straight) | 2000 kg | 3527 lb |
| Max. height of bucket pivot point | m | ft |
| Max. dump height | m | ft |
| Steering | Hydrostatic (all-wheel) steering | |
| Steering angle | 2 x 38 ° | 2 x 38 ° |
| Fuel tank capacity | 60 l | 16 US gal |
| Hydraulic tank capacity | l | US gal |

Standard Package - 280

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Monday, August 13, 2012

