

# GP 4000 Premium Portable Generator

Item Number: 0620977

# GP 4000

## Rugged and powerful generators for the most demanding jobsites

>> Designed for construction rental and other demanding applications, these high performance, portable generators deliver unmatched tool starting and voltage regulation in a rugged, compact package. Built the Wacker Neuson way, with heavy-duty frames and premium components to provide long, trouble-free operation even in abusive environments. Ideal for powering high starting amperage tools such as compressors, grinders, fusion welders, saws, pressure washers as well as all of your Wacker Neuson electric- powered pumps, breakers, drills, concrete vibrators, etc. <<



## Additional Advantages

- Best in class tool starting and voltage regulation due to unique step-start generator technology with AVR (automatic voltage regulation) and separate excitation winding.
- Unique GFCI (neutral bonded to ground) sensor system eliminates common GFI outlet failures while offering personal protection on all receptacles including 240 Volt. Meets the latest NEC and OSHA jobsite standards.
- Full wrap-around frame with dual cross-member support, high impact polyethylene fuel tank and heavy duty shock-mounting combine to provide outstanding impact protection.
- A super quiet muffler allows for versatile operation.
- Unique auto-idle control with time delay system automatically reduces the engine to a low speed reducing fuel consumption, noise and wear
- The folding central lifting eye and integrated wheel kit make these compact generators easy to transport and store.
- Full power switch for maximum 120V power output or 120V/240V power.
- Available with the high performance Wacker Neuson OHC engine (on GP2600 and GP4000) or Honda OHV engine, both feature low oil shutdown.



Description	Metric	Imperial
Length x width x height	685 x 530 x 537 mm	27 x 21 x 21 in
Dry Weight	69 kg	152 lb
Shipping weight (including packaging)	71 kg	157 lb
Shipping size	711 x 546 x 589 mm	28 x 21.5 x 23 in
Maximum output	4000 W	4000 W
Continuous Output	3600 W	3600 W
Continuous AC amps	30 / 15 A	30 / 15 A
Voltage A.C.	120 / 240 V	120 / 240 V
AC circuit breaker amps	17	
Frequency	60 Hz	60 Hz
Phase	1 ~	1 ~
Power factor (1 phs / 3 phs)	1	1
Engine Type	Wacker WM270	
Starting system	Recoil	Recoil
Displacement	265 cm <sup>3</sup>	16 in <sup>3</sup>
Max. Rated Power at Rated Speed*	6.6 kW at 4000 rpm	9 hp at 4000 rpm
Operating speed	3600 1/min	3600 rpm
Power Rating Specification	SAE J1349	SAE J1349
Fuel tank capacity	19 l	5 US gal
Fuel consumption	2.4 l/h	0.64 US gal/h
Oil tank capacity	1 l	1 US qt
Running time	7.8 h	7.8 h
AC outlet receptacles	125V, 20 A Duplex, GFI 125V, 20 A Duplex	125V, 20 A Duplex, GFI 125V, 20 A Duplex

### Standard Package - GP 4000

Include operator's manual and parts book. Some standard packages include wheel kit. Battery sold separately.

Please refer to our [Price List and Ordering Guide](#) for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Monday, August 13, 2012

