

WL 25 Multi-purpose Wheel Loader, 2.5t

Item Number: 0620587

WL 25

The productive, multi-purpose wheel loader that can do it all.

>> Wacker Neuson's WL 25 wheel loader moves with the highest precision around every job site. This multi-purpose loader features high break-out force and large lifting capacity. The spacious cab with ergonomic controls and 360-degree visibility provide for a more comfortable and safer unit, increasing productivity. The rugged WL 25 loader offers better capacities, higher reach, differential lock and more creature comforts as opposed to the WL 18. <<



Additional Advantages

- Efficient operation where engine efficiency reduces operating costs
- Higher payloads provide better break-out force and lifting capacity
- Ergonomic design with operator comforts that improve productivity
- Higher resale value as compared to alternative skid steer loaders
- Operating elements arranged ergonomically next to the driver's seat; multi-functional singlelever control; additional lever for 3rd control circuit
- Vibration-dampened ROPS (Roll Over Protection System) and FOPS (Falling Object Protection System) located on the rear frame as part of the fully enclosed cab.
- Excellent visibility; infinitely adjustable steering column; platform is side tilting for better serviceability
- Parallel lift frame and universal coupler system
- Hydraulically operated centrally-articulated pendulum steering



Description	Metric	Imperial
Engine Type	Perkins (404 C - 15), 4-cylinder	
Engine Power (at 2800 rpm)*	24.6 kW	33 hp
Speed	0 - 20 km/h	0 - 12.43 mph
Bucket capacity	0.35 m ³	0.46 yd ³
Drive	Hydrostatic drive with steering wheel	
Axles	Rigid axles	
Differential lock	100% electric-hydraulic switchable front and rear axle	
Brakes	Hydrostatic drive and hub brake with braking-inching pedal, operating on all 4 wheels	
Standard tires	10 x 16.5 EM (Earth moving tires)	
Overall length	4087 mm	160.9 in
Max. height of bucket pivot	2862 mm	113 in
Max. dump height	2050 mm	81 in
Height of cab	2280 mm	89.8 in
Inside turning radius	1330 mm	52.4 in
Outside turning radius	2590 mm	102 in
Operating weight	2520 kg	5555.6 lb
Total width, standard	1210 mm	47.6 in
Hydraulic pump flow	45 lpm	11.9 gpm
System pressure	185 bar	2683 psi
Hydraulic lifting capacity	2521.7 kg	5559.5 lb
Breake-out force	1989 kg	4471.4 lb
Tipping load with bucket	1626 kg	3585.7 lb
Tipping loads with bucket (articulated)	1339 kg	2951.9 lb
Tipping loads with pallet fork (straight)	1249 kg	2753.6 lb
Tipping loads with pallet fork (articulated)	1021 kg	2250.9 lb

Standard Package - WL 25

includes operator's manual and parts book

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Monday, August 13, 2012

