



## GPS 9700V

Portable Generators



### Portable power, when and where you need it

High performance portable generator to fit your job and budget. This Wacker Neuson generator is built for construction, industrial, commercial, domestic and farm applications. It features an heavy-duty lightweight compact frame that provides job site protection while reducing storage space requirements. An integrated lifting eye to accommodate a 3-inch hook makes for easy transport.

- Oversized fuel tank for long, uninterrupted operation also features an easy to read fuel gauge. A super quiet muffler allows for operation under all conditions.
- An auto-idle control with time delay automatically reduces the engine to a low speed decreasing fuel consumption, noise and wear on connected electrical loads.
- Premium grade ground fault interrupter (GFI) for weather resistance and increased durability. The 120-volt duplex receptacles break circuit due to a ground fault condition.
- Units feature a 120/240-volt power switch providing full 120-volt power or shared power from both 120 and 240-volt receptacles.
- Overhead valve engine with automatic decompression and maintenance-free electronic ignition system provide consistent and easy starting.

### Technical specifications



## Portable Premium Generators

### Dimensions

L x W x H Overall	31.5 x 25.125 x 23.75 in
L x W x H Shipping	32 x 25.75 x 25.5 in
Weight Dry	221 lb
Shipping weight without Fuel	236 lb

### Operating data

Operating weight with Fuel	268 lb
Circuit breaker AC - 1 Phase 2 Pole	39 A
Receptacles AC Outlet	(2) 120V, 20A Duplex
Receptacles AC Outlet	120V, 30A Twist Lock L5-30R
Receptacles AC Outlet	240V, 20A Twist Lock L6-20R
Receptacles AC Outlet	120/ 240V, 30A Twist Lock L14-30R

### Electrical system

Electrical power Max. Output	9,700 W
Electrical power Continuous Power	9,300 W
Voltage AC - 1 Phase	120/ 240 V
Current AC - 1 Phase	80.8/ 40.4 A
Frequency	60 Hz
Power factor	1 cos $\Phi$ 1~
Generator model	AVR With Brushes
Generator insulation (class) Class	H
Power Rating Specification	SAE J1940

### Engine / Motor

Engine / Motor	B&S Vangaurd
Engine / Motor manufacturer	356,447
Cylinder	1
Displacement	34.75 in <sup>3</sup>
Operating performance	18 kW
RPM / speed Operating	3,600 rpm
Tank capacity Oil	1.75 US qt



Tank capacity Fuel	7.4 US gal
Fuel type	Gasoline
Fuel consumption	1.64 US gal/h
Runtime	4.51 h

**Please note**

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.  
Copyright © 2016 Wacker Neuson SE.