



3001

Wheel Dumpers



Operator comfort and high productivity: 3001

This mid size dumper features a 6,600 lb (3-metric ton) payload capacity, power swivel material handling and hydrostatic permanent four wheel drive as standard. The hydrostatic drive system offers user-friendly controls, eliminating the need to change gears. The 3001 offers superior performance, the drive system automatically provides torque when and where it is needed. With no clutch to wear or gears to grind, hydrostatic drive eliminates the high parts and labor costs associated with replacing these components. ROPS and heated cab versions are available.

- Operator station is easily accessible from both sides for added convenience.
- Swivel bucket allows material to be unloaded on either side of the unit for ultimate versatility.
- Four-wheel drive provides perfect traction in difficult terrain. Articulated steering with central hose routing allows for tight turning radius and protection of the hoses.
- Dashboard displays a full range of dials/indicator lights such as fuel gauge, low fuel warning light and parking brake light for operator convenience.
- Engine cover lifts high giving excellent access to all the service points

Technical specifications



3001 Tier IV

Operating data

Payload	6,614 lb
Net weight	5,313 lb
Skip capacity - water	301.6 US gal
Skip capacity - struck	1.7 yd ³
Skip capacity - heaped	2.3 yd ³

Engine / Motor

Engine / Motor manufacturer	Perkins
Engine / Motor type	403F-15T
Engine / Motor	Diesel
Engine performance	36.2 hp
Displacement	91.3 in ³
Travel speed	14 mph
Articulation angle	36 °
Pendulum angle	15 °
Turning radius	152 in
Gradeability	50 %
L x W x H	157 x 70 x 105 in

3001 Tier III

Operating data

Payload	6,614 lb
Net weight	5,578 lb
Skip capacity - water	242 US gal
Skip capacity - struck	1.7 yd ³
Skip capacity - heaped	2.3 yd ³

Engine / Motor

Engine / Motor manufacturer	Yanmar
Engine / Motor type	3TNV88
Engine / Motor	Diesel



Engine performance acc. to ISO 3046/1	34 hp
Displacement	100 in ³
Travel speed	14 mph
Articulation angle	37 °
Pendulum angle	15 °
Turning radius	144 in
Gradeability	50 %
L x W x H	163 x 70 x 105 in



**WACKER
NEUSON**
all it takes!

Dimensions

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2016 Wacker Neuson SE.